



LITHIUM

MODEL: ATLS12-120BT

CERTIFICATIONS
 UL1642 (Cell), CE (Pack), IEC62133 (Cell), UN38.3 (Cell / Pack), IEC62619 (Cell), ROHS (Cell)



BLUETOOTH MONITORING FOR ANDROID AND IOS



Specifications

Electrical Specifications	Nominal Voltage	12.8V	
	Nominal Capacity	120 Ah	
	Nominal Power	1536 Wh	
	Parallel Connection	max 4 units	
	Series Connection	max 4 units	
	Circuit Protection	Overcharge, over discharge, over current, high temperature, short cuircuit, cell balancing	
	Cycle life	3000 cycles @100% DOD 6000 cycles @80%DOD	
Charge Specifications	Charge Profile	CC @ 0.2C to 14.4V, then CV @ 14.4V until current $\leq 0.01C$ (CC/CV)	
	Max Charge Voltage	14.4 \pm 0.2V	
	Standard Current	24A	
	Max Current	60A	
Discharge Specifications	Standard Current	24A	
	Max Continuous Current	120A	
	Cut-off Voltage	10V	
Environmental Specifications	Charge Temperature	0°C to 55°C	60 \pm 25% Relative Humidity
	Discharge Temperature	-20°C to 60°C	
	Storage Temperature	-5°C to 45°C	
Mechanical Specifications	Dimensions, mm	305x169x210 (Group 27)	
	Approx Weight, kg	13.5	
	Terminal type	M8	
	Case Material	Plastic ABS	
	IP Rating	IP65	
	Cell Type	Cylindrical LiFePO ₄	

Circuit Protection	Characteristic	Parameters
Overcharge protection	High voltage protection	15V
	Reset/Recovery voltage	14.4V
	Reset trigger	below reset value
	Time delay	10s
Over discharge protection	Low voltage protection	10V
	Reset/Recovery voltage	10.4V
	Reset trigger	Cut Load, Auto release
	Time delay	10s
Overcurrent	Max charge current protection	145A
	Charge current protection reset	140A
	Time delay	10s
	Max discharge current protection	800A
	Discharge current protection reset	750A
	Time delay	10s

Circuit Protection	Characteristic	Parameters
High temperature	Max charge temperature	65°C
	Recovery point	55°C
	Time delay	10s
	Max discharge temperature	65°C
	Recovery point	55°C
	Time delay	10s
	MOSFET over temperature protection	85°C
Cell balance	Balance condition voltage (per cell)	$\geq 3.3V$
	Balance condition voltage difference (cell)	30mv
	Balanced closed voltage difference (cell)	20mv
	Cell balance current	30mA
Short circuit protection	Short circuit protection	850A
	Time delay	150 μ s



LITHIUM

MODEL: ATLS12-120BT

CERTIFICATIONS
UL1642 (Cell), CE (Pack), IEC62133 (Cell), UN38.3 (Cell / Pack), IEC62619 (Cell), ROHS (Cell)




BLUETOOTH MONITORING FOR ANDROID AND IOS




Characteristics Curve


Charging Characteristics (0.5C @ 25°C)




Discharging Characteristics (0.2C, 0.5C, 1C @ 25°C)




Different Temperature Capacity Curve



Typical Charge Time Curve



Different Temperature Self Discharge Curve



Different DOD Discharge Cycle Life Curve

